



| PIN | SYMBOL | PIN | SYMBOL |
|-----|--------|-----|--------|
| 1 | LED-A | 26 | G1 |
| 2 | LED-A | 27 | G0 |
| 3 | LED-A | 28 | R7 |
| 4 | LED-K | 29 | R6 |
| 5 | LED-K | 30 | R5 |
| 6 | VCOM | 31 | R4 |
| 7 | DVDD | 32 | R3 |
| 8 | MODE | 33 | R2 |
| 9 | DE | 34 | R1 |
| 10 | VS | 35 | R0 |
| 11 | HS | 36 | GND |
| 12 | B7 | 37 | DCLK |
| 13 | B6 | 38 | GND |
| 14 | B5 | 39 | L/R |
| 15 | B4 | 40 | U/D |
| 16 | B3 | 41 | VGH |
| 17 | B2 | 42 | VGL |
| 18 | B1 | 43 | AVDD |
| 19 | B0 | 44 | RESET |
| 20 | G7 | 45 | NC |
| 21 | G6 | 46 | VCOM |
| 22 | G5 | 47 | DITHB |
| 23 | G4 | 48 | GND |
| 24 | G3 | 49 | NC |
| 25 | G2 | 50 | NC |

| | | | | | |
|-----------------|-----------|------------------|-----------|-----------------------|-----------------|
| Screen Size: | 7.0(inch) | OP Temperature: | -20~+70°C | Backlight Characters: | 160mA |
| View Direction: | Full View | ST Temperature: | -30~+80°C | Luminance + LED: | 300nit/24PCS |
| Grey scale: | IPS | Analog Voltage: | 3.3V | Driver IC : | EK79001/EK73215 |
| Display mode: | IPS | Digital Voltage: | | Reminder : | |

ROHS must be complied Unspecified tolerance is /0.25mm

| | |
|---------------|------------------------|
| Outline NAME: | SL-7.0-1024600-AWMN-05 |
| VER: A | U: mm |
| APPROVED | S: 1:1 |
| CHECKED | Date: 20210612 |
| DRAWN | |