



21.7V(typ)/20mA

Screen Size:	4.3(inch)	OP Temperature:	-30~+80°C	Backlight Characters:	20mA/21.7V(typ)	Outline NAME:	SL-4.3-480272-FWMN-15
View Direction:	Full viewing	ST Temperature:	-30~+80°C	Luminance + LED:	350nit/TYP	VER:A	U: mm S: 1:1 Date: 20221228
Grey scale:	/	Analog Voltage:	3.3V	Driver IC:	NV3041A	APPROVED	CHECKED
Display mode:	IPS-Glare	Digital Voltage:		Reminder			DRAWN

Pin assignment	PIN	SYMBOL
1	VLED-	
2	VLED+	
3	GND	
4	VDD	
5	NC	
6	NC	
7	DB0	
8	DB1	
9	DB2	
10	DB3	
11	DB4	
12	DB5	
13	NC	
14	NC	
15	DB6	
16	DB7	
17	DB8	
18	DB9	
19	DB10	
20	DB11	
21	NC	
22	NC	
23	DB12	
24	DB13	
25	DB14	
26	DB15	
27	NC	
28	NC	
29	RST	
30	DISP	
31	CS	
32	WRX	
33	SDA	
34	RDX	
35	DCX	
36	TE	
37	NC/(XR)	
38	NC/(YD)	
39	NC/(XL)	
40	NC/(YU)	

ROHS must be complied Unspecified tolerance is /0.2mm