



A ± 0.2 mm
20mA/21.7V

Pin assignment	Pin SYMBOL
1	VLED-
2	VLED+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	PCLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	NC/(XFR)
38	NC/(YD)
39	NC/(XL)
40	NC/(YU)

Screen Size:	4.3(inch)	OP Temperature:	-10~+60°C	Backlight Characters:	20mA/21.7V	Outline	NAME: SL-4.3-480272-ATMN-82
View Direction:	12 O'clock	ST Temperature:	-20~+70°C	Luminance + LED:	300nit/PPCS	VER: A	U: mm
Grey scale:	6 O'clock	Analog Voltage:	3.3V	Driver IC:	ST7282	APPROVED	CHECKED
Display mode:	TN	Digital Voltage:		Reminder			DRAWN

ROHS must be complied. Unspecified tolerance is ±0.25mm